



INDUSTRIJA NAFTE, d.d.

SD NAFTAPLIN

Sektor istraživanja i
proizvodnje NIP za JIE

**Successful work-over activities in
function of safety and enhanced
productivity
at Deep Podravina wells:
Stari Gradac-3, Kalinovac-8,
Kalinovac-19 and Stari Gradac-6**

SUMMARY

POGON MOLVE

- presentation of succesful workovers on the wells :
 - StG-3 (May - August 2010)
 - Kal-8 (December – January 2010)
 - Kal-19 (November 2009)
 - StG-6 (December 2010)
- significance of the formation protection
- isolation of flooded intervals
- new interval perforating
- production increasing in Deep Podravina district

DEEP PODRAVINA PRODUCTION FIELDS

POGON MOLVE

- MOLVE
- KALINOVAC
- STARI GRADAC
- GOLA DUBOKA

Contents of acid gases:

CO₂ ~ 10% - 56%

H₂S ~ 100 – 1000ppm

Hg, RSH, Cl⁻

high P, high T

CORROSIVE CONDITIONS

PRODUCTION EQUIPMENT:

Tubing 13%Cr – 25%Cr, SSSV, SD, seal units, permanent packer with seal bore extension ...

Production casing – packer fluid with pressure control

StG-3 WORKOVER – WELL SAFETY

POGON MOLVE

BRINGING WELL INTO PRODUCTION

- well
- water
- sliding
- N₂ ~
- well
- clean



STSI ~ 2,2 x 10⁶ kn
duration 56 days

šljarič


Kal-8

POGON MOLVE

DETAILED WELL ANALYSIS

- Geological survey report: DST
- EPILOG, PL, CBL, EK – diagrams
- HD measurements – interpretation
- Analysis of possibilities and ways of perforating
- System analysis IPR – VLP of future production

new interval
new interval
Gas production (m³/d x 1 000)
Water production (m³/d)



Kal-19 BEFORE CHEMICAL TREATMENT

POGON MOLVE

Before:

$P_t = 65 \text{ bar}$

$Q_g = 41000 \text{ m}^3/\text{d}$


$Q_c = 19 \text{ m}^3/\text{d}$

$Q_v = 2 \text{ m}^3/\text{d}$

$\text{Sal.} = 0,233 \text{ g/l}$

SKIN ~ 63

$\Delta p_{\text{SKIN}} \sim 110 \text{ bar}$



Kal-19 BEFORE CHEMICAL TREATMENT

POGON MOLVE



Acid washing tubing – CT
 $1+1,4 \text{ m}^3$; 7,5% HCl+N₂



Acidizing job – bull-head
 $2+2+2 \text{ m}^3$; 7,5% HCl+N₂



Kal-19

AFTER

CHEMICAL TREATMENT

POGON MOLVE

After:

$P_t = 140 \text{ bar}$

$Q_g = 98700 \text{ m}^3/\text{d}$

$Q_c = 33,6 \text{ m}^3/\text{d}$

$Q_v = 6,4 \text{ m}^3/\text{d}$

$\text{Sal.} = 1,75 \text{ g/l}$

- **CAPEX: 910 345 HRK**
- **NPV: 115,8 MHRK**
- **Profitability: 96,68 HRK/HRK**


ROI ~ 8 days

StG-6

POGON MOLVE

EXPECTED PRODUCTION

Skin = 12.2 (skin removed 75 %)
 $p_t = 68 \text{ bar}$, $Q_g = 66\,066 \text{ m}^3/\text{d}$



SCALE DETECTION

CONCLUSION

POGON MOLVE

- Detailed well analysis
 - Isolation of flooded interval
 - Special cementing procedure
 - Opening of new production interval
 - stimulation
- Production layer protection
 - Experience - CaCO_3
- Goal increased production

POGON MOLVE

SRETNNO